

SAFETY DATA SHEET

MANGANESE NITRATE SOLUTION 14% Mn

Section 1 - Identification

Product Manganese Nitrate Solution 14% Mn

Manufacturer TradeMark Nitrogen Corp.

Address 1216 Old Hopewell Road, Tampa, FL 33619

Phone (813) 626-1181 (800) 452-3107

24 Hour Chemtrec Emergency (800) 424-9300

Contact

Section 2 - Hazard Identification







Recommended Use:

fertilizer.

Used in agriculture as a micro nutrient

GHS03

GHS05

GHS07

Signal Word: WARNING

Hazard Statements:

H272 May intensify fire; Oxidizer

H302 Harmful if swallowed

H314 Causes severe skin burns and eye damage

H315 Causes skin irritation

H319 Causes serious eye irritation

H333 May be harmful if inhaled

H335 May cause respiritory irritation

Precautionary

Statements:

P101 If medical advice is needed, have product container or label at hand

P102 Keep out of reach of children

P103 Read label before use

P202 Do not handle until all safety precautions have been read and understood

P220 Keep / store away from clothing and combustible materials

P233 Keep container tightly closed

P260 Do not breathe dust / fumes / gas / mist / vapours / spray

P262 Do not get in eyes, on skin, or on clothing

P264 Wash hands thoroughly after handling

P270 Do not eat, drink or smoke when using or handling this product

P273 Avoid release to the environment

P280 Wear protective gloves / protective clothing / eye protection / face protection

P285 In case of inadequate ventilation wear respiratory protection

P301 + P312 If swallowed, call a POISON CENTER or doctor / physician if you feel unwell

P302 + P352 IF ON SKIN: wash with plenty of soap and water

P304 + P341 IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in position comfortable for breathing

P305 + P351 + IF IN EYES: Rinse caustiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing P338

P331 Do NOT induce vomitting

P370 + P380 In case of fire: Evacuate area

P402 + P404 Store in a dry place. Store in closed container

P501 Dispose of contents / container in accordance with local, state and federal regulations

Section 3 - Co					
Ingredients	Component	CAS. No.	Percent by	Percent as Metal	
	Manganese	10377-66-9	Weight 46%	14.0% Mn	
	Nitrate	10077 00 0	1070	11.070 14111	
	$(Mn(NO_3)_2)$				
	Water (H ₂ 0)	7732-18-5	Balance		
Section 4 - Fir	st Aid Measu	res			
Inhalation	If inhaled: Remove person to fresh air and keep comfortable for breathing. Provide artificial respiration if necessary. Seek medical attention if necessary.				
Skin Contact	If on skin (or hair): Take off all contaminated clothing. Rinse skin with soap and water for at least 15 minutes.				
Eye Contact	If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing for at least 15 minutes. Seek medical attention if irritation persists.				
Ingestion	If swallowed: Do NOT induce vomiting . Drink large amounts of water. Never give anything by mouth to an unconscious person. See promt medical attention.				
Acute Health	Harmful if swallowed or inhaled. Destructive to mucous membranes and upper respiratory tract, eyes and skin. Redness and irritation				
Hazards	of tissue may occur. Ingestion can lead to stomach aches and nausea.				
Chronic Health	Prolonged exposure to manganese compounds may result in manganese poisoning, not usually fatal but disabling. Target organs				
Hazards	include respiratory system, central nervous system, lungs, blood and kidneys. re Fighting Measures				
Section 5 – Fir Suitable			ite to the intensity o	of the fire. Wear self-c	ontained breathing apparatus and full protective gear.
Extinguishing Techniques &	The second of th				
Equipment					
Chemical	Under fire conditions, this product behaves as an oxidizer. Contact with oxidizable substances may result in ignition, violent combustio				
Hazards From Fire	or explosion. This material may decompose and produce acrid vapors, manganese compounds and oxides of nitrogen.				
Special Fire Fighting	Use water to extinguish fire. Do not use dry chemicals or foams. CO2 or halon may provide limited control. Fire fighters should wear appropriate protective equipment, full turn-out gear, and utilize a SCBA (self contained breathing apparat Keep upwind. Fight fire from a protected location.				
Procedures					
NFPA Rating	Health - 2 (Mo	oderate)			
	Fire - 0 (Least)				
	Reactivity - 1 (Slight) OXY - Oxidizer				
Other	Do not allow run-off from fire fighting to enter drains or water courses.				
Section 6 – Ac	_		· ·		
Personal	Manganese Nitrate is an oxidizer. Avoid contact with skin. Avoid splashing. Prevent exposure to spilled material with the use of proper				
Precautions Protective	PPE.				
Equipment	PPE should include gloves, goggles, face shield and level C protective suit.				
Containment	Control the flow of product using dikes of soil, sand bags or other commercially available inert sorbent socks or booms.				
In Case of Spill	Absorb product with inert absorbent. Avoid splashing or spraying. Contain and pick up spill in diked area. Prevent discharge to sewers				
		. If uncontaminated	, recover and re-us	e.	
	fe Handling & Storage				
Precautions for Safe Handling & Storage	Store in a well ventilated cool dry place. Containers should be kept closed and labled properly. Liquid is an oxidizer and may cause fire with combustibles. Do not heat (weld, cut, braze) a container with manganese nitrate in it.				
Incompatibility	Avoid contact with combustibles (wood, paper, cotton). Keep away from fire. Extreme heat may result in decomposition of material to toxic fumes of nitrogen oxides.				
Section 8 – Ex		ols / Personal Pro	otection		
Exposure Limits	<u>. </u>	Permissible Exposure Limit	Threshold Limit Value	Short Term Exposure Limit	Immediately Dangerous to Life
	Manganese	F 3	0.0 3	Not Established	or Health
	Nitrate (Mn(NO ₃) ₂)	5 mg/m³ (as Mn) ⁽¹⁾	0.2 mg/m ³ (TWA) ⁽¹⁾	MOT PSTANIISTIEU	500 mg/m³ (as Mn) ⁽²⁾
	Water (H ₂ O)	Not Established	Not Established	Not Established	Not Established
	(1) Limits are listed under Manganese and inorganic compounds (OSHA / ACGIH).				
	(2) Limits are listed under Manganese compounds, N.O.S. (NIOSH)				
Engineering		•	•	, ,	/ashing facilities should be available

Provide ventilation sufficient to maintain exposure below PEL/TWA/TLV. Washing facilities should be available.

Engineering Controls Personal Eyes Chemical safety goggles and full face sheild. Contact lenses should not be worn when handling product.

Equipment Hands Impervious chemical protective gloves.

Respiratory None required under normal conditions. Self contained respiratory equipment should be used under spill

conditions.

Protective Clothing

Chemical resistant protective clothing.









Gloves Goggles

Face Shield Protective Clothing

Section 9 - Physical & Chemical Properties

Appearance and Light pink & odorless Specific Gravity 1.58 at 68°F Odor

Boiling Point > 212°F (>100°C) at 1 atmosphere Solubility in Water No Data Available Freezing Point No Data Available Evaporative Rate No Data Available

Vapor PressureNo Data AvailablepH< 1.0</th>Weight per
Gallon13.2 lbs/galSalt-Out Temp< 54.9°F (12.7°C)</td>

Flash Point No Data Available Auto Ignition Temp Not Flammable

Flammability No Data Available LEL No Data Available Limits

UEL No Data Available

Section 10 - Stability & Reactivity

Reactivity Product may act as an oxidizer.

Stability Product is corrosive at standard temperature and pressure.

Hazardous polymerization will not occur.

Reactions

Conditions to Elevated temperatures may cause container to rupture.

Avoid

Incompatible Organic or other oxidizable materials, copper or brass.

Materials

Hazardous Extreme heat may cause decomposing to toxic fumes of nitrogen oxides.

Decomposition Products

Section 11 – Toxicology Information

Routes of Inhalation, ingestion or skin/eye absorption

Exposure

Symptoms and Eyes Mild irritant.
Signs of Skin Mild irritant.

Exposure Inhalation Of gases or mist causes irritation to the upper respiratory system, including the mucous membrane, the nose, mouth

and throat. Chemical burns may occur if inhaled. Cough, fever, nausea, headache, shortness of breath and sore

throat are possible.

Ingestion may cause upset stomach.

Long Term Prolonged xposure to manganese compounds may result in manganese poisoning, not usually fatal but disabling. Target organs

Effects include respiratory system, central nervous system, lungs, blood and kidneys.

Carcinogen The International Agency for Research on Cancer has not classified manganese nitrate for its carcinogenic potential (IARC 1987).

Toxicity 500 mg/m3 (as Mn) is Immediately Dangerous to Life and Health (NIOSH).

Section 12 - Ecological Information

Toxicity

No Data Available

Persistence of

No Data Available

Degradability

Bioaccumulation No Data Available

Potential

Section 13 - Disposal Considerations

Waste Disposal must be done in accordance with local, state and federal environmental regulations. Place waste in an appropriate container

with correct labeling.

Section 14 - Transport Information

This material is hazardous as defined by 49 CFR 172.101 by the US Department of Transportation

UN ID Number UN 3093

Proper Shipping

UN 3093 Corrosive, Oxidizing Liquid, N.O.S. (Manganese Nitrate Solution)

Name Hazard Class 8 (5.1) Packing Group PG II US DOT Label Corrosive Marine Pollutant No

Emergency 140

Response Guide Number





This material is regulated as a Dangerous Good per the IMDG Code

UN ID Number UN 3093

Proper Shipping

Name UN 3093 Corrosive, Oxidizing Liquid, N.O.S. (Manganese Nitrate Solution)

Hazard Class Packing Group PG II Label Corrosive





This material is regulated as a Dangerous Good per the IATA Code

UN ID Number UN 3093

Proper Shipping

UN 3093 Corrosive, Oxidizing Liquid, N.O.S. (Manganese Nitrate Solution) Name

Hazard Class 8 (5.1) Packing Group PG II Label Corrosive





Section 15 - Regulatory Information

United States -SARA Hazard Category

This product has been reviewed according to the EPA Hazard Categories promulgated under Sections 311 and 312 of Title III of the Superfund Amendments and Reauthorization Act (SARA) and is considered, under applicable definitions, to meet the following categories:

SARA Title III

Fire - No Pressure - No Reactive - Yes Acute - Yes Chronic - No This product contains the following substances subject to the reporting requirements of Title III (EPCRA) of the Superfund Amendments

Information

and Reauthorization Act of 1986 and 40 CFR Part 372: Chemical CAS No. CERCLA RQ (lbs.) SARA Reporting

302 304 313 10377-66-9 Yes⁽¹⁾ Manganese N/A Nο Nο

Nitrate

(1) As manganese compounds

CERCLA / Superfund, 40 CFR Part 117, If this product contains components subject to substances designated as CERCLA reportable Quantity (RQ) Substances, it will be designated in the above table with the RQ value in pounds. If there is a release of RQ Substance to the environment, notification to the National Response Center, Washington DC (800-424-8802) is required.

302 **TSCA**

Manganese nitrate solution is a hydrated form of nitric acid, manganese (II) salt, which is listed on the TSCA inventory.

Section 16 - Other Information

Issue Date: 1/4/2024

Date of Revision January 2024 revision prepared in accordance with 29 CFR 1910.1200 Appendix D to meet Global Harmonization Standards.

Disclaimer

The information contained in this SDS refers only to the specific material designated and does not relate to any process or use with any other materials. This information is furnished free of charge and is based on data believed to be accurate and reliable as of the date hereof. It is intended for use by persons possessing technical knowledge at their own discretion and risk. Since actual use is beyond our control, no warranty, expressed or implied, and no liability is assumed by TradeMark Nitrogen Corp. in conjunction with the use of this information. Nothing herein is to be construed as a recommendation to infringe any patents. TradeMark Nitrogen Corp. assumes no responsibility for injury to vendee or third persons proximately caused by abnormal use of the material even if reasonable safety procedures are followed. Furthermore, vendee assumes the risk in his use of the material.